

MOTORIZED DRAPERY SYSTEMS

SlimLine Motorized Drapery System

Sleek & Slim motorized drapery track that can be easily curved to meet your installation requirements. Spans up to 19' unspliced and pulls up to 135lbs of fabric with single motor or 220lbs with tandem system.





Features:

- Slim profile track with only 8" bending radius.
- SlimLine system can be built with either low voltage plug-in or battery operated Finesse motor, or line voltage HD motor.
- System available with pinch pleat or Snap-On carriers.
- 6-channel RF remote control & 4-channel RF wireless wall switch work with every Finesse drape & shade system.
- Built-in LV port for contact closure control and RS485 interface are available for direct connection to any Automation system. (with the exception of HD 45W that requires external controls)
- Standard track colour is powder coated white, track can be custom painted.

Specifications:


	Finesse Z-Wave	Finesse Li-Ion	Finesse RS485	HD45W-Tandem
- Rated Power:	24VDC/1.5A	14.8VDC/0.8A	24VDC/1.5A	110VAC / 2 x 0.9A
- Rated torque:	1.2Nm	0.6Nm	1.2Nm	2 x 1.2Nm
- Max Pulling Capacity	100lbs	50lbs	100lbs	220lbs
- Track profile: 1" x 1-1/4" aluminum extrusion 6063 T5				
- Transmission: 6mm polyurethane thermoplastic timing belt reinforced w/Kevlar cords				
- Maximum system width unspliced: 232"				
- Maximum load capacity: 2lbs per carrier / total capacity depends on track width (please refer to capacity tables)				
- Bracket spacing: 20" standard (16" at stack recommended)				
- All KS brackets applicable				



Bending / Curving:

Tracks can be curved to precise specifications, including single, multiple and reverse curves. Template required for bending - please call customer service for instructions.

Minimum radius for curve: 8"



Please contact customer service for quotation

For high capacity applications please refer to Heavy Duty Motorized Drapery system.